

LA-SWM3-10G0008PB-S150w

Multi-Gigabit Layer 3 Managed PoE Switch 10G Copper

8x10M/100M/1G/2.5G/5G/10G RJ45



Overview

LA-SWM3-10G0008PB-S150w is Layer 3 10Gbps Ethernet PoE++ Switch, designed for high bandwidth and power-hungry devices like Wi-Fi7/6E APs, NAS units, thin clients, and surveillance systems. Boasting 8x10GBASE-T copper ports, it ensures flexible connectivity with extended reach.

The capability to reach a high speed of 10Gbps over copper cabling which helps to accelerate the performance of large data transmission. 10Gbps data transmission with the existing Cat6/Cat6A UTP cabling, meaning the speed can be increased without costs. It can definitely give you the speed you demand and its Plug and Play makes installation easy.

Features

- 8 x PoE+ ports with 150w total power budget
- Port 1 supports PoE++ standard with 90w
- Unlock the real WiFi 6 with 10/2.5Gbps PoE ports
- Easy-to-use web-based management interface
- Support Web / TFTP / HTTP firmware upgrade
- Managed features include access control lists, VLAN, IGMP snooping, QoS, RMON, SNMP trap, and syslog for monitoring and flexible network integration.
- Desktop (Optional wall+machine hanger parts)

Specifications

Fixed Port	8*10M/100M/1G/2.5G/5G/10Gbps RJ45 PoE
PoE Ports	1 port: IEEE802.3af/at/bt (HiPoE) Max 90W/port 2-8 ports: IEEE802.3af/at Max 30W/port
Console Ports	1*Console port
Reset Key	1
PoE Pin	Af/at/bt: 12+ 45+ ; 36- 78- Af/at: 12+ 36-
PoE Bridge	Max 150w
CPU	Cortex-A9 1GHz
DDR	4G DDR3
FLASH	512MBytes
RAM	512MBytes
Bandwidth	160Gbps
Packet Forwarding	115.84Mpps
MAC	16K
Buffer	4.1 Mbit SRAM Packet Buffer
Jumbo Frame	Jumbo packets up to 9216 bytes
VLAN Address	4K
Link Aggregation	Supports 128 trunk groups with up to 8 members per group
L3 Routing	IPV4 supports 1024; IPV6 supports 512;
QoS Queue	8
Transmission Distance	10BASE-T: Cat3,4,5 UTP(≤250 meter) 100BASE-TX: Cat5 or later UTP(150 meter) 1000BASE-TX: Cat6 or later UTP(150 meter)

	SFP:100M/1G/10G single-mode multi-mode optical module, the maximum distance is $\leq 120\text{km}$ (depending on the optical module)
LED Indicator	PWR:Power LED 1-8: PoE - Work LED; Link_Network Connection LED PoE port: Orange PoE LED, green network connection LED
Power	Max 180W (AC 100~240V 50/60HZ Max 2.2A)
Operating Temperature/Humidity	-10~+55°C; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75°C; 5%~95% RH Non coagulation
Product /Packing size (L*W*H)	335mm*195mm*45mm 410mm*278mm*95mm
N.W/G.W (kg)	1.76kg/2.4kg
Lightning Protection level	6KV 8/20us; IP30
Installation	Rack-mount (optional machine hanger spare parts)
Certificate	CE-EMC EN55032; CE-LVD EN62368; FCC Part 15 Class B; RoHS
Warranty	Whole device for 1 year (Accessories not included)

Port

Port Shutdown	Support
Port Speed	Support auto-negotiation, full-1000, full-100, half-100, full-10, half-10
Flow Control	support full-duplex IEEE 802.3x, half-duplex back pressure
Storm Control	Supports rate limit for broadcast, multicast, and DLF packets
Storm Constrain	Support the detection of broadcast packets, multicast packets, or unicast packets on the port, shutdown the port if the rate is over the threshold.
Port Mirror	Support
Port Rate Limit	Support port ingress and egress rate limit
Link Aggregation	Support manual link aggregation Support LACP dynamic link aggregation Supports up to 32 aggregation groups, each group up to 8 ports Support source MAC, destination MAC, source destination MAC, source IP, destination IP, source destination IP routing strategy
Port Isolate	Support
Jumbo Frame	Support up to 16KB packet
Redundant Port	Support

MAC

MAC Table Capacity	16K
MAC Table Management	Support
Forwarding mode	Support IVL forwarding mode
Static MAC Address	Support
MAC Address Binding	Support
MAC Address Filtering	Support
MAC Learning Control	Control the MAC learning based on port
VLAN	
Number of VLANs	4K
802.1q-based VLAN	Support
MAC-based VLAN	Support
IP-based VLAN	Support
Protocol-based VLAN	Support
Voice VLAN	Support
VLAN Mapping	Support 1:1 mapping
QinQ	Support basic QinQ Support flexible QinQ
Reliability	
Spanning Tree Protocol	Support STP/RSTP/MSTP
Port Loop Detection	Support
EAPS	Support
ERPS	Support G.8032/Y.1344
LLDP	Support LLDP & LLDP-MED
UDLD	Fully compatible with CISCO's UDLD protocol
VLLP (VRRP Layer-2 Loop Protection)	Support, Only used with VRRP
L3	
ARP	Support static and dynamic ARP
Static Route	Support
VLAN Interface	Support 32 VLAN interfaces
RIP	Support RIP v1/v2
OSPF	Support OSPFv2

Policy Route	Support
VRRP	Support
Multicast	
Static Multicast MAC Address	Support
IGMP SNOOPING	Support IGMP SNOOPING v1/v2/v3 Support IGMP Querier Support IGMP SNOOPING Filter
MVR	Support
GMRP	Support
ACL	
Standard IP-based ACL	Support
Extended IP based ACL	Support
MAC IP-based ACL	Support
MAC ARP-based ACL	Support
ACL Port Filtering	Support
Time-based ACL	Support
QoS	
Port Queue Number	8
Port Queue Scheduling Mode	Support WRR, RR, WDRR, SP
Port-based Classification	Support
802.1p-based Classification	Support
DSCP-based Classification	Support
ACL-based Classification	Support
QoS Policy	Support packets mapping to queue Support COS or DSCP Remarking Support rate limits of data flow Support data flow statistics Support mirroring of data flow
DHCP	
DHCP Client	Support
DHCP Snooping	Support
DHCP Relay	Support
DHCP Server	Support

DHCP option 82	Support
Management	
CLI Management	Support Console, Telnet and SSH
WEB Management	Support HTTP and HTTPS
SNMP Management	Support SNMP v1, v2c Support SNMP TRAP Support lots of standard and private MIBs
User Management	Support multiple user management
Log Management	Support local log management Support SYSLOG
RMON	Support RMON 1, 2, 3 and 9 groups
Cluster Management	Support NDP Support NTDP Support manual and automatic joining of cluster groups Support cluster unified management
Configuration File	Support uploading and downloading configuration file
Upgrade software	Support
Clock Management	Support local clock management Support SNTP
Security	
Switch Management Security	Support enabling and disabling TELNET, WEB and SNMP services Support TELNET, WEB and SNMP services to bind to standard IP ACLs Support for limiting the number of TELNET connections
CPU Protection	The switch's own security protection prevents large data streams from attacking the switch itself.
AAA	Support 802.1x Support RADIUS Supports authentication, authorization, and accounting through RADIUS server Support port-based and MAC-based 802.1x Support 802.1x guest VLAN
IP MAC Binding	Support static configuration of IP, MAC and port binding
DHCP SNOOPING	Support dynamic ARP binding to prevent ARP spoofing Support dynamic IP, MAC and port binding Support fixed port to connect to DHCP server to prevent private connection to DHCP server
Prevent ARP Spoofing	Support manually configuring MAC ARP-based ACL rules to prevent ARP spoofing. Support the DHCP SNOOPING function. During the process of obtaining an IP address by DHCP, the switch dynamically binds ARP to the port to prevent ARP spoofing.

Debugging

PING	Support
------	---------

TRACEROUTE	Support
------------	---------

TELNET Client	Support
---------------	---------

Ordering Information**P/N****Description**

LA-SWM3-10G0008PB-S150w

Multi-Gigabit Layer 3 Managed PoE Switch 10G Copper
8x10M/100M/1G/2.5G/5G/10G RJ45



<https://www.lanaotek.com>



Specifications & design are subject to change without prior notice.

For more details, please email to info@lanaotek.com. Copyright©2024 lanaotek.com All Rights Reserved