

LA-SWM3-10G1200-S

L3 Managed 10G Switch, 12x100/1000M/10G SFP+



Overview

LA-SWM3-10G1200-S is a L3 managed 10G Switch, it is designed to meet the needs of modern enterprise and data center environments. Equipped with 12 SFP+ ports that support 100M/1G/10G speeds, it offers flexible connectivity options for a variety of devices, from high-speed servers to edge devices in complex networks. The switch's robust management features provide complete control over network traffic, ensuring efficiency, security, and scalability in demanding network environments.

Features

- 12x100/1000M/10G SFP+ ports
- Advanced Layer 2 and Layer 3 Switching
- Comprehensive Security Features
- Flexible Management Options
- High Availability and Redundancy
- Energy Efficient

Specifications

Fixed Port	12x100/1000M/10G SFP+
Console Port	1 console port
Reset Key	1
CPU	Cortex-A9 600Mhz
DDR	8G DDR3
FLASH	512Mbytes
RAM	1024Mbytes
Bandwidth	512Gbps
Packet Forwarding	190.46Mpps
MAC	16K
Buffer	2Mbit SRAM Packet Buffer
Jumbo Frame	Jumbo packets up to 9 KB.
VLAN Address	4K
Link Aggregation	Supports 128 trunk groups with up to 8 members per group
L3 Routing	IPV4 supports 768; IPV6 supports 384;
QoS Queue	8
Transmission Distance	10BASE-T: Cat3,4,5 UTP(≤250 meter) 100BASE-TX: Cat5 or later UTP(150 meter) 1000BASE-TX: Cat6 or later UTP(150 meter) SFP: 100M/1G/10G single-mode multi-mode optical module, the maximum distance is ≤ 120km (depending on the optical module)
LED Indicator	PWR: Power LED SYS: System LED 1-12: 10G SFP connection indicator
Power	Built-in power AC: 100-240Vac 50-60Hz 0.6A max 45W
Operating Temperature/Humidity	-10~+55°C 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75°C 5%~95% RH Non coagulation
Product /Packing size (L*W*H)	440mmx200mmx45mm 515mmx300mmx95mm
N.W/G.W (kg)	2.1kg/2.7kg
Lightning	6KV 8/20us
Protection level	IP30
Installation	Rack-mount (optional machine hanger spare parts)

Certificate CE-EMC EN55032; CE-LVD EN62368;
FCC Part 15 Class B; RoHS

Warranty Whole device for 1 year (Accessories not included)

Port

Number of Fiber 10G or 1G ports

Port Speed Support negotiate, full-1000, full-100, half-100, full-10, half-10

Flow Control support full-duplex IEEE 802.3x, half-duplex back pressure

Storm Control Supports rate limit for broadcast, multicast, and DLF packets

Storm Constrain Support the detection of broadcast packets, multicast packets, or uni cast packets on the port, shutdown the port if the rate is over the threshold.

Port Mirror Support

Port Rate Limit Support port ingress and egress rate limit

Link Aggregation Support manual link aggregation
Support LACP dynamic link aggregation
Supports up to 32 aggregation groups, each group up to 8 ports
Support source MAC, destination MAC, source destination MAC, source IP, destination IP, source destination IP routing strategy

Port Isolate Support

Jumbo Frame Support up to 16KB packet

Redundant Port Support

MAC

MAC Table Capacity 16K

MAC Table Management Support

Forwarding Mode Support IVL forwarding mode

Static MAC Address Support

MAC Address Binding Support

MAC Address Filtering Support

MAC Learning Control Control the MAC learning based on port

VLAN

Number of VLANs 4K

802.1q-based VLAN Support

MAC-based VLAN Support

IP-based VLAN Support

Protocol-based VLAN Support

Voice VLAN	Support
VLAN Mapping	Support 1:1 mapping
QinQ	Support basic QinQ Support flexible QinQ
Reliability	
Spanning Tree Protocol	Support STP/RSTP/MSTP
Port Loop Detection	Support
EAPS	Support
ERPS	Support G.8032/Y.1344
LLDP	Support LLDP & LLDP-MED
UDLD	Fully compatible with Cisco's UDLD protocol
VLLP (VRRP Layer-2 Loop Protection)	Support, Only used with VRRP
L3	
ARP	Support static and dynamic ARP
Static Route	Support
VLAN Interface	Support 32 VLAN interfaces
RIP	Support RIP v1/v2
OSPF	Support OSPFv2
Policy Route	Support
VRRP	Support
Multicast	
Static Multicast MAC Address	Support
IGMP SNOOPING	Support IGMP SNOOPING v1/v2/v3 Support IGMP Queerer Support IGMP SNOOPING Filter
MVR	Support
GMRP	Support
ACL	
Standard IP-based ACL	Support
Extended IP based ACL	Support
MAC IP-based ACL	Support
MAC ARP -based ACL	Support

ACL Port Filtering	Support
Time-based ACL	Support
QoS	
Port Queue Number	8
Port Queue Scheduling Mode	Support WRR, RR, WDRR, SP
Port-based Classification	Support
802.1p-based Classification	Support
DSCP - based Classification	Support
ACL - based Classification	Support
QoS Policy	Support packets mapping to queue Support COS or DSCP Remarking Support rate limits of data flow Support data flow statistics Support mirroring of data flow
DHCP	
DHCP Client	Support
DHCP Snooping	Support
DHCP Relay	Support
DHCP Server	Support
DHCP Option 82	Support
Management	
CLI Management	Support Console, Telnet and SSH
WEB Management	Support HTTP and HTTPS
SNMP Management	Support SNMP v1, v2c Support SNMP TRAP Support lots of standard and private Mibs
User Management	Support multiple user management
Log Management	Support local log management Support SYSLOG
RMON	Support RMON 1, 2, 3 and 9 groups
Cluster Management	Support NDP Support NTDP Support manual and automatic joining of cluster groups Support cluster unified management
Configuration File	Support uploading and downloading configuration file

Upgrade Software	Support
Clock Management	Support local clock management Support SNTP
Security	
Switch Management Security	Support enabling and disabling TELNET, WEB and SNMP services Support TELNET, WEB and SNMP services to bind to standard IP ACLs Support for limiting the number of TELNET connections
CPU Protection	The switch's own security protection prevents large data streams from attacking the switch itself.
AAA	Support 802.1x Support RADIUS Supports authentication, authorization, and accounting through RADIUS server Support port-based and MAC-based 802.1x Support 802.1x guest VLAN
IP MAC Binding	Support static configuration of IP, MAC and port binding
DHCP SNOOPING	Support dynamic ARP binding to prevent ARP spoofing Support dynamic IP, MAC and port binding Support fixed port to connect to DHCP server to prevent private connection to DHCP server
Prevent ARP Spoofing	Support manually configuring MAC ARP - based ACL rules to prevent ARP spoofing. Support the DHCP SNOOPING function. During the process of obtaining an IP address by DHCP, the switch dynamically binds ARP to the port to prevent ARP spoofing.
Debugging	
PING	Support
TRACEROUTE	Support
TELNET Client	Support

Ordering Information

P/N	Description
LA-SWM3-10G1200-S	L3 Managed 10G Switch, 12x100/1000M/10G SFP+



<https://www.lanaotek.com>



Specifications & design are subject to change without prior notice.

For more details, please email to info@lanaotek.com. Copyright©2024 lanaotek.com All Rights Reserved.